

Product Information



Utica Gas Oil # 11

DESCRIPTION

Cross Utica Gas Oils are non-detergent naphthenic based fuel oils manufactured from select naphthenic crude streams. These fuel oils are designed for refinery feed stock, marine bunker fuels and boilers.

TEST NAME	TEST METHOD	SPECIFICATIONS		
		Minimum	Maximum	Typical
Viscosity, cSt @ 40° C	D-445	-	-	1,604.70
Viscosity, cSt @ 100° C	D-445	45	60	42.86
Viscosity, SUS @ 100° F	D-2161	-	-	7,433.6
Viscosity, SUS @ 210° F	D-2161	-	-	201.1
Gravity, API, 60° F	D-4052	15.0	19.0	18.5
Specific Gravity, 60/60° F	D-1250	-	-	0.9433
Pounds per Gallon @ 60° F	D-1250	-	-	7.608
Flash, COC, °C (°F)	D-92	250 (480)	-	321 (610)
Pour Point, °C (°F)	D-97	-	12 (54)	-1 (30)
Color	D-1500	-	8.0	L 8.0
Sulfur, Mass %	D-4294	-	2.0	0.95

Cross Oil Manufacturing Specification – CU-3010

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Safety Data Sheets available on request.

CROSS OIL REFINING & MARKETING, INC.

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ www.crossoil.com