

Product Information



Utica Gas Oil # 9

DESCRIPTION

Cross Utica Gas Oils are non-detergent naphthenic based fuel oils manufactured from select naphthenic crude streams. These fuel oils are designed for refinery feed stock, marine bunker fuels and boilers.

TEST NAME	TEST METHOD	SPECIFICATIONS		
		Minimum	Maximum	Typical
Viscosity, cSt @ 40° C	D-445	-	-	649.48
Viscosity, cSt @ 100° C	D-445	-	-	25.64
Viscosity, SUS @ 100° F	D-2161	-	-	3008.7
Viscosity, SUS @ 210° F	D-2161	-	-	123.0
Gravity, API, 60° F	D-4052	-	-	18.8
Specific Gravity, 60/60° F	D-1250	-	-	0.9415
Pounds per Gallon @ 60° F	D-1250	-	-	7.845
Flash, COC, °C (°F)	D-92	-	-	321 (610)
ASTM Color	D-1500	-	-	L 6.5

Cross Oil Item No. –; CU-3009

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Safety Data Sheets available on request.

CROSS OIL REFINING & MARKETING, INC.

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ www.crossoil.com