

Product Information



Cross B-40

DESCRIPTION

Cross B Series are severely hydro treated naphthenic process oils manufactured from select crude streams. B Series oil offer low pour point good solvency and color stability. They are ideal for production blending, adhesives, plastics and extended rubber.

TEST NAME	TEST METHOD	SPECIFICATIONS		
		Minimum	Maximum	Typical
Viscosity, cSt @ 40° C	D-445	3.0	4.89	4.87
Viscosity, cSt @ 100° C	D-445			1.63
Viscosity, SUS @ 100° F	D-2161			40
Viscosity, SUS @ 210° F	D-2161			32
Gravity, API, 60° F	D-4052	24.6	31.3	27.3
Specific Gravity, 60/60° F	D-1250			0.8911
Pounds per Gallon @ 60° F	D-1250			7.420
Flash, COC, °C (°F)	D-92	93 (200)		100 (212)
Color	D-1500		L1.5	L 1.0
Sulfur, Mass %	D-4294			0.06
DMSO Extract, wt.%	IP-346		3.0	< 3.0

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Material Safety Data Sheets available on request.

CROSS OIL REFINING & MARKETING, INC.

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ www.crossoil.com