

## Product Information



# Cross B-50

### DESCRIPTION

**Cross B Series** are severely hydro treated naphthenic process oils manufactured from select crude streams. B Series oil offer low pour point good solvency and color stability. They are ideal for production blending, adhesives, plastics and extended rubber.

TEST NAME	TEST METHOD	SPECIFICATIONS		
		Minimum	Maximum	Typical
Viscosity, cSt @ 40° C	D-445	5.7	7.66	6.68
Viscosity, cSt @ 100° C	D-445			1.98
Viscosity, SUS @ 100° F	D-2161			49.2
Viscosity, SUS @ 210° F	D-2161			32.8
Gravity, API, 60° F	D-4052	25.9	30.9	27.0
Specific Gravity, 60/60° F	D-1250			0.8927
Pounds per Gallon @ 60° F	D-1250			7.434
Flash, COC, °C (°F)	D-92	93 (199)		96 (205)
Pour Point, °C (°F)	D-97		-48 (-55)	-57 (-70)
Color	D-1500		1.5	L 1.0
Sulfur, Mass %	D-4294			0.10
DMSO Extract, wt. %	IP-346		3.0	< 3.0

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Material Safety Data Sheets available on request.

### CROSS OIL REFINING & MARKETING, INC.

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ [www.crossoil.com](http://www.crossoil.com)