

## Product Information



# Heavy Hydrotreated Naphtha

**DESCRIPTION** Refined and hydrotreated naphtha with ultra-low sulfur levels produced from naphthenic base oils

TEST NAME	TEST METHOD	SPECIFICATIONS		
		Minimum	Maximum	Typical
Viscosity, cSt @ 40° C	D-445			4.28
Viscosity, cSt @ 100° C	D-445			1.48
Viscosity, SUS @ 100° F	D-2161	30	60.0	40.9
Viscosity, SUS @ 210°F	D-2161			31.1
Flash, °C/°F, pmcc	D-93			< 23 / <73
Color	D-1500			L 0.5
Gravity, API	D-4052	25.0		27.6
Pounds per gallon	D-1250			7.406
Sulfur, % Wt.	D-4294			0.02
Total Acid No.	D-977			0.01
Kauri Butanol Value	D-1133			43
Cetane Index	D-976			37
Aniline Point, °C/°F	D-611			61 / 142
Distillation, °C/°F	D-86			
IBP		Typical		134 / 273
50%		Typical		283 / 541
EP		Typical		391 / 736

### CROSS OIL REFINING & MARKETING, INC.

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ [www.crossoil.com](http://www.crossoil.com)

## Product Information

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Material Safety Data Sheets available on request.

---

**CROSS OIL REFINING & MARKETING, INC.**

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ [www.crossoil.com](http://www.crossoil.com)

---