

Product Information



Utica Gas Oil # 7

DESCRIPTION

Cross Utica Gas Oils are non-detergent naphthenic based fuel oils manufactured from select naphthenic crude streams. These fuel oils are designed for refinery feed stock, marine bunker fuels and boilers.

TEST NAME	TEST METHOD	SPECIFICATIONS		
		Minimum	Maximum	Typical
Viscosity, cSt @ 40° C	D-445	212	250	232.3
Viscosity, cSt @ 100° C	D-445			12.74
Viscosity, SUS @ 100° F	D-2161			1272
Viscosity, SUS @ 210° F	D-2161			70.9
Gravity, API, 60° F	D-4052	15.0	19.0	18.1
Specific Gravity, 60/60° F	D-1250			0.9459
Pounds per Gallon @ 60° F	D-1250			7.877
Flash, COC, °C (°F)	D-92	218 (425)		232 (450)
Pour Point, °C (°F)	D-97		-18 (0)	-15 (+5)
Color	D-1500		D 8.0	L 4.5
Sulfur, Mass %	D-4294		1.0	0.50
Refractive Index @ 20°C	D-1747			1.524
Aniline Point, (°C) / °F	D-611			(77) 171
Aromatic Carbon Atoms, %Ca	D-2140			26
Naphthenic Carbon Atoms, %Cn	D-2140			32
Paraffinic Carbon Atoms, %Cp	D-2140			42
Volatility, %	EPA 24			0.8

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Material Safety Data Sheets available on request.

CROSS OIL REFINING & MARKETING, INC.

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ www.crossoil.com