

## Product Information



# Cross B-40

### DESCRIPTION

**Cross B Series** are severely hydro treated naphthenic process oils manufactured from select crude streams. B Series oil offer low pour point good solvency and color stability. They are ideal for production blending, adhesives, plastics and extended rubber.

TEST NAME	TEST METHOD	SPECIFICATIONS		
		Minimum	Maximum	Typical
Viscosity, cSt @ 40° C	D-445	3.0	4.89	4.87
Viscosity, cSt @ 100° C	D-445	-	-	1.63
Viscosity, SUS @ 100° F	D-2161	-	-	40
Viscosity, SUS @ 210° F	D-2161	-	-	32
Gravity, API, 60° F	D-4052	24.6	31.3	27.3
Specific Gravity, 60/60° F	D-1250	-	-	0.8911
Pounds per Gallon @ 60° F	D-1250	-	-	7.420
Flash, COC, °C (°F)	D-92	93 (200)	-	100 (212)
Color	D-1500	-	L1.5	L 1.0
Sulfur, Mass %	D-4294	-	-	0.06
DMSO Extract, wt. %	IP-346	-	3.0	< 3.0

### REACH Registration

CAS No. 64742-53-6

CAS No. 64742-52-5

**Pre-registration** 02-2118612511-56-0000

**Registration** 01-2119467170-45-0030

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**Cross™** is a trademark of Cross Oil Refining & Marketing, Inc.. All other marks are property of their respective owners.

**CROSS OIL REFINING & MARKETING, INC.**

SMACKOVER, AR 71762 ■ USA ■ PHONE 800 864-6275 ■ [www.crossoil.com](http://www.crossoil.com)