



EBONITE H-180

BLACK OILS

Ebonite Oils are asphaltic lubricant or compound for in the tyre industry and rubber compounding. The Ebonite series can also be used greases, open gears, chains and inks applications.

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL
		Min	Max	
Physical Properties				
Viscosity, cSt @ 40° C	D-445	-	-	
Viscosity, cSt @ 100° C	D-445	36	40.9	40.83
Viscosity, SUS @ 100° F	D-2161	-	-	
Viscosity, SUS @ 210° F	D-2161	180	200	199.8
Gravity, API, 60° F	D-4052	-	-	17.2
Specific Gravity, 60/60° F	D-1250	-	-	0.9516
Pounds per Gallon @ 60° F	D-1250	-	-	7.924
Flash, COC, °C (°F)	D-92	-	-	260(500)
Pour Point, °C (°F)	D-97	-	-	-7(+20)
Color	D-1500	-	-	BLACK
Volatility, 22 hrs @ 225°F	D-972	-	-	<0.1
Sulfur, % wt.	D-4294	-	-	0.825

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Safety Data Sheets available on request.

Cross™ and Ebonite™ are trademarks of Cross Oil Refining & Marketing, Inc.. All other marks are property of their respective owners.

Cross Oil Refining & Marketing, Inc.

Smackover, AR 71762 | USA | Phone 800 864-6275 | www.crossoil.com

Product Data Sheet Revision 01/2020