

## Product Information



# Heavy Hydrotreated Distillate

**DESCRIPTION**                      Refined and hydro-treated distillate with ultra-low sulfur levels produced from naphthenic base oils

TEST NAME	TEST METHOD	SPECIFICATIONS		
		Minimum	Maximum	Typical
Viscosity, cSt @ 40° C	D-445			2.50
Viscosity, cSt @ 100° C	D-445			1.30
Viscosity, SUS @ 100° F	D-2161			34.6
Viscosity, SUS @ 210°F	D-2161			30.4
Flash, °C/°F, pmcc	D-93			< 23 / <73
Color	D-1500		1.0	L 0.5
Gravity, API	D-4052	25.0		34.0
Pounds per gallon	D-1250			7.119
Sulfur, % Wt.	D-4294		0.10	.02
Total Acid No.	D-977			0.01
<b>Distillation, °C/°F</b>				
IBP				93 / 199
50%	D-86	Typical		260 / 500
90%				330 / 626
EP				427 / 800

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Safety Data Sheets available on request.

**Cross™** is a trademark of Cross Oil Refining & Marketing, Inc.. All other marks are property of their respective owners.