



# HEAVY HYDROTREATED NAPHTHA

DISTILLATES

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL
		Min	Max	
<b>Physical Properties</b>				
Viscosity, cSt @ 40 C	D-445			4.28
Viscosity, cSt @ 100° C	D-445			1.48
Viscosity, SUS @ 100° F	D-2161	30	60.0	40.9
Viscosity, SUS @ 210°F	D-2161			31.1
Flash, °C/°F, pmcc	D-93			< 23 / <73
Color	D-1500			L 0.5
Gravity, API	D-4052	25.0		27.6
Pounds per gallon	D-1250			7.406
Sulfur, % Wt.	D-4294			0.02
Total Acid No.	D-977			0.01
Kauri Butanol Value	D-1133			43
Cetane Index	D-976			37
Aniline Point, °C/°F	D-611			61 / 142
<b>Distillation, °C/°F</b>				
IBP		Typical		134 / 273
50%		Typical		283 / 541
EP		Typical		391 / 736

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Safety Data Sheets available on request.

Cross™ is trademarks of Cross Oil Refining & Marketing, Inc.. All other marks are property of their respective owners.

**Cross Oil Refining & Marketing, Inc.**

Smackover, AR 71762 | USA | Phone 800 864-6275 | [www.crossoil.com](http://www.crossoil.com)

Product Data Sheet Revision 01/2020