



CROSS L-150

BASE OILS

Cross L Series are severely hydro treated naphthenic base oils manufactured from select crude streams. They offer low pour point, good solvency and color stability. They are ideal for production blending and exhibit excellent solubility with additive systems.

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL
		Min	Max	
Physical Properties				
Viscosity, cSt @ 40° C	D-445	28.79	30.71	29.78
Viscosity, cSt @ 100° C	D-445	-	-	4.61
Viscosity, SUS @ 100° F	D-2161	-	-	156.0
Viscosity, SUS @ 210° F	D-2161	-	-	41.1
Gravity, API, 60° F	D-4052	-	-	24.1
Specific Gravity, 60/60° F	D-1250	-	-	0.9094
Pounds per Gallon @ 60° F	D-1250	-	-	7.576
Flash, COC, C (F)	D-92	166 (330)	-	175 (347)
Pour Point, C (°F)	D-97	-	-32 (-25)	-37 (-35)
Color	D-1500	-	1.5	L 1.0
Aniline Point, C (°F)	D-611	-	-	77 (171)
Molecular Weight	D-2502	-	-	335
Refractive Index @ 20° C	D-1747	-	-	1.498
Refractivity Intercept	D-2159	-	-	1.040
Sulfur, Mass %	D-4294	-	0.10	0.04
UV Absorptivity, 260 NM	D-2008	-	-	3.0
Volatility, 22 hr/225° F, % Mass	D-972	-	-	6.1
DMSO Extract, wt. %	IP-346	-	3.0	< 3.0

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Safety Data Sheets available on request.

Cross™ are trademarks of Cross Oil Refining & Marketing, Inc.. All other marks are property of their respective owners.

Cross Oil Refining & Marketing, Inc.

Smackover, AR 71762 | USA | Phone 800 864-6275 | www.crossoil.com

Product Data Sheet Revision 01/2020