
SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

Product ID: 531215
Product Name: Cross L-150
Revision Date: Sep 01, 2015 **Date Printed:** Sep 14, 2015
Version: 2.0 **Supersedes Date:** Apr 16, 2015
Manufacturer's Name: Cross Oil Refining & Marketing, Inc.
Address: 484 E. 6th Street Smackover, AR, US, 71762
Emergency Phone: CHEMTREC (800) 424-9300
Information Phone: 870-864-7500
Fax:
Product/Recommended Uses: Process oil, Chemical carrier, Lubricant.

SECTION 2) HAZARDS IDENTIFICATION

Classification of the substance or mixture:

Not a hazardous substance or mixture according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) and Council Directive 1999/45/EC and its subsequent amendments.

SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0064742-52-5	MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC	85% - 100%

SECTION 4) FIRST-AID MEASURES

Inhalation:

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Get medical advice/attention if exposed, feel unwell (headache, nausea, drowsiness etc.) or are concerned.

Skin Contact:

Rinse/wash with lukewarm, gently flowing water and mild soap for 5 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

Eye Contact:

If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

Ingestion:

Rinse mouth. If you feel unwell or if concerned: Get medical advice/attention.

If more than several mouthfuls have been swallowed, give two glasses of water (16 Oz.). Get medical attention.

Notes:

High velocity injection of grease under the skin may result in serious injury. If left untreated, the affected area is subject to infection, disfigurement, lack of blood circulation and may require amputation. When dispensed by high-pressure equipment, this material can easily penetrate the skin and leave a bloodless puncture wound. Material injected into a finger can be deposited into the palm of the hand and in rare occasions up to the elbow. Within 24 to 48 hours the patient may experience swelling, discoloration, and throbbing pain in the affected area. Immediate treatment by a surgical specialist is recommended.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Dry chemical, foam, carbon dioxide, water spray or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Water or foam may cause frothing. If leak or spill has not ignited, use water spray to cool the containers and to provide protection for personnel attempting to stop the leak.

Unsuitable Extinguishing Media:

Do not use water in a jet.

Specific Hazards in Case of Fire:

Hazardous combustion products may include: Toxic levels of carbon monoxide, carbon dioxide, irritating aldehydes and ketones.

Fire-fighting Procedures:

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Stay upwind and avoid smoke and fumes. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel.

Special Protective Actions:

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

WARNING: Product can burn in a fire.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure:

Immediately turn off or isolate any source of ignition. Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Clean up immediately. Contain spill. Wipe up or add suitable absorbent, non-combustible, inert material such as sand, sawdust, etc. to spill area and shovel into appropriate container for disposal. Local authorities should be advised immediately if required or if significant spillages cannot be contained.

Ventilate area.

Recommended equipment:

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions:

Avoid breathing vapor or mist. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Will not produce vapors unless heated to temperatures of ~300 °F.

Environmental Precautions:

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

SECTION 7) HANDLING AND STORAGE

General:

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Ventilation Requirements:

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements:

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.

Minimum feasible handling temperature should be maintained. Periods of exposure to high temperature should be minimized. Water contamination should be avoided.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection:

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin protection:

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. If the respirator is the sole means of protection, use a full-face supplied air respirator.

Supplied air respiratory protection should be used for cleaning large spills or upon entry into tanks, vessels, or other confined spaces.

Appropriate Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC	500	2000			1							

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC							

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	7.614 lb/gal
% Solids By Weight	0.000%
Density VOC	0.464 lb/gal
% VOC	6.100%
VOC Actual	0.464 lb/gal
VOC Actual	55.650 g/l
Specific Gravity	0.912

Appearance	Clear; light amber to dark liquid
Odor Threshold	N.A.
Odor Description	Mild hydrocarbon odor
pH	N.A.
Water Solubility	Insoluble
Flammability	N/A
Flash Point Symbol	N.A.

Flash Point	341.6 °F
Viscosity	29.64 cSt @ 40°C (104°F)
Lower Explosion Level	N.A.
Upper Explosion Level	N.A.
Vapor Pressure	< 0.007 mmHg
Vapor Density	1+
Freezing Point	N.A.
Melting Point	N.A.
Low Boiling Point	680 °F
High Boiling Point	N.A.
Auto Ignition Temp	N.A.
Decomposition Pt	N.A.
Evaporation Rate	N.A.
Partition Coefficient: n-Octanol/Water	N.A.

SECTION 10) STABILITY AND REACTIVITY

Stability:

Stable

Conditions to Avoid:

Avoid heat, flame, and contact with strong oxidizing agents.

Hazardous Polymerization:

Will not occur.

Incompatible Materials:

Reacts violently with strong oxidizers.

Hazardous Decomposition Products:

Evolves toxic levels of carbon monoxide, carbon dioxide, irritating aldehydes and ketones when heated to combustion.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation:

Prolonged or repeated contact may cause skin irritation.

Serious Eye Damage/Irritation:

Irritating, but will not permanently injure eye tissue.

Respiratory/Skin Sensitization:

No Data Available

Germ Cell Mutagenicity:

No Data Available

Carcinogenicity:

The highly refined mineral oil contains <3% DMSO extract as measured by IP 346, hence the classification of a carcinogen need not apply.

Reproductive Toxicity:

No Data Available

Specific Target Organ Toxicity - Single Exposure:

No Data Available

Specific Target Organ Toxicity - Repeated Exposure:

No Data Available

Aspiration Hazard:

No Data Available

Acute Toxicity:

No Data Available

LD50 (Rodent - rat, Oral) : >5000 mg/kg, Toxic effects : Details of toxic effects not reported other than lethal dose value.

LD50 (Rodent - rabbit, Administration onto the skin) : >2000 mg/kg, Toxic effects : Details of toxic effects not reported other than lethal dose value.

SECTION 12) ECOLOGICAL INFORMATION

Toxicity:

This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration.

This product may cause gastrointestinal distress in birds and mammals through ingestion.

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration.

Persistence and Degradability:

Is rapidly biodegradable. Biodegradation is possible with 100 to 120 days in aerobic environments at temperatures above 70 °F (21 °C).

Other Adverse Effects:

No Data Available.

Bio-accumulative Potential:

0064742-52-5 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC

Contains constituents with the potential to bioaccumulate.

Mobility in Soil:

0064742-52-5 MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC

Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal:

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information:

Bulk Shipping Description: Does not apply to bulk oil shipping.

Non-Bulk Shipping Description: Does not apply to non-bulk oil shipping.

Identification Number: Not applicable.

Hazard Classification: Not applicable.

Other: See 49 CFR for additional requirements for descriptions, allowed modes of transport and packaging. For more information concerning spills during transport, consult latest DOT Emergency Response Guidebook for Hazardous Materials Incidents, DOT P 5800.3.

IMDG Information:

This material is not classified as dangerous under IMDG regulations.

IATA Information:

This material is not classified as dangerous under IATA regulations.

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0064742-52-5	MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (MILD) HEAVY NAPHTHENIC	85% - 100%	SARA312,TSCA


SECTION 16) OTHER INFORMATION INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS


Glossary:

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ - Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA - Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

Version 2.0:

Changes made on: Section 1, Section 2 and Section 9
Revision Date: Sep 1, 2015
Please contact the supplier for further information on the version history



Chronic : 

DISCLAIMER

Information provided in this Safety Data Sheet is considered accurate and reliable based on information issued from internal and outside sources to the best of Cross Oil Refining & Marketing, Inc.'s knowledge; however, Cross Oil Refining & Marketing, Inc. makes no representations, guarantees or warranties, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such information or the result to be obtained from the use thereof or as to the sufficiency of information herein presented. Cross Oil Refining & Marketing, Inc. assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.

This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Cross Oil Refining & Marketing, Inc., must rely upon information provided by the material manufacturers or distributors.