



CROSS B-100

Base Oils

Cross B Series are severely hydro treated naphthenic process oils manufactured from select crude streams. B Series oil offer low pour point good solvency and color stability. They are ideal for production blending, adhesives, plastics and extended rubber.

| TEST DESCRIPTION | TEST METHOD | SPECIFICATIONS | | TYPICAL |
|----------------------------|-------------|----------------|-------|-----------|
| | | Min | Max | |
| Physical Properties | | | | |
| Viscosity, cSt @ 40° C | D-445 | 18.76 | 20.81 | 20.08 |
| Viscosity, cSt @ 100° C | D-445 | | | 3.64 |
| Viscosity, SUS @ 100° F | D-2161 | | | 106.6 |
| Viscosity, SUS @ 210° F | D-2161 | | | 43.9 |
| Gravity, API, 60° F | D-4052 | 22.5 | 27.5 | 24.2 |
| Specific Gravity, 60/60° F | D-1250 | | | 0.9088 |
| Pounds per Gallon @ 60° F | D-1250 | | | 7.571 |
| Flash, COC, C (F) | D-92 | | | 149 (300) |
| Pour Point, C (°F) | D-97 | | | -43 (-45) |
| Color | D-1500 | | L2.0 | L1.5 |
| DMSO Extract, wt. % | IP-346 | | 3.0 | < 3.0 |

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Safety Data Sheets available on request.

Cross™ are trademarks of Cross Oil Refining & Marketing, Inc.. All other marks are property of their respective owners.

Cross Oil Refining & Marketing, Inc.

Smackover, AR 71762 | USA | Phone 800 864-6275 |

www.crossoil.com

9-2020