



# CROSS B-200

## BASE OILS

Cross B Series are severely hydro treated naphthenic process oils manufactured from select crude streams. B Series oil offer low pour point good solvency and color stability. They are ideal for production blending, adhesives, plastics and extended rubber.

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL
		Min	Max	
<b>Physical Properties</b>				
Viscosity, cSt @ 40° C	D-445	38.4	43.3	41.08
Viscosity, cSt @ 100° C	D-445			5.39
Viscosity, SUS @ 100° F	D-2161	200	225	218
Viscosity, SUS @ 210° F	D-2161			44.4
Viscosity Index	D-2270			31
Gravity, API, 60° F	D-4052	21.0	26.0	22.1
Specific Gravity, 60/60° F	D-1250			0.9212
Pounds per Gallon @ 60° F	D-1250			7.671
Flash, COC, °C (°F)	D-92	145 (295)		150 (300)
Pour Point, °C (°F)	D-97		-29 (-20)	-37 (-35)
Color	D-1500		2.5	L 1.0
Aniline Point, C/F	D-611			81 (178)
Sulfur, Mass %	D-4294			0.10
Aromatic Carbon Atoms, %Ca	D-2140			18
Naphthenic Carbon Atoms, %Cn	D-2140			37
Paraffinic Carbon Atoms, %Cp	D-2140			45
Asphaltenes, Mass %	D-2007			0
Polar Compounds, Mass %	D-2007			1.67
Aromatics, Mass %	D-2007			34.51
Saturates, Mass %	D-2007			63.82
DMSO Extract, wt. %	IP-346		3.0	< 3.0

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

**Health And Safety Information** See separate Safety Data Sheets available on request.

Cross™ are trademarks of Cross Oil Refining & Marketing, Inc.. All other marks are property of their respective owners.