



UTICA GAS OIL #11

GAS OILS

Utica Gas Oils are non-detergent naphthenic based fuel oils manufactured from select naphthenic crude streams. These fuel oils are designed for refinery feed stock, marine bunker fuels and boilers.

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL
Physical Properties		Min	Max	
Viscosity, cSt @ 40° C	D-445	-	-	6121
Viscosity, cSt @ 100° C	D-445	60	100.0	96.02
Viscosity, SUS @ 100° F	D-2161	-	-	35,751
Viscosity, SUS @ 210° F	D-2161	-	-	471.3
Gravity, API, 60° F	D-4052	-	-	15.4
Specific Gravity, 60/60° F	D-1250	-	-	0.963
Pounds per Gallon @ 60° F	D-1250	-	-	8.022
Flash, COC, °C (°F)	D-92	-	-	305 (581)
Pour Point, °C (°F)	D-97	-	+12	12 (54)
Aniline Point, °C (°F)	D-611	-	-	98 (208)
ASTM Color	D-1500	-	8.0	D 8.0
Sulfur, Mass %	D-4294	-	2.000	2.024
Refractive Index @ 20° C	D-1747	-	-	1.54
Volatility, Mass %	EPA 24	-	-	0.5

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Safety Data Sheets available on request.

Cross™ is a trademark of Cross Oil Refining & Marketing, Inc., All other marks are property of their respective owners.

Cross Oil Refining & Marketing, Inc.

Smackover, AR 71762 | USA | Phone 800 864-6275 | www.crossoil.com

Product Data Sheet Revision 01/2012