



UTICA GAS OIL #7

GAS OILS

Utica Gas Oils are non-detergent naphthenic based fuel oils manufactured from select naphthenic crude streams. These fuel oils are designed for refinery feed stock, marine bunker fuels and boilers.

TEST DESCRIPTION	TEST METHOD	SPECIFICATIONS		TYPICAL
		Min	Max	
Physical Properties				
Viscosity, cSt @ 40° C	D-445	260	340	303.8
Viscosity, cSt @ 100° C	D-445	-	-	14.91
Viscosity, SUS @ 100° F	D-2161	-	-	1674
Viscosity, SUS @ 210° F	D-2161	-	-	79.7
Gravity, API, 60° F	D-4052	-	-	17.2
Specific Gravity, 60/60° F	D-1250	-	-	0.9514
Pounds per Gallon @ 60° F	D-1250	-	-	7.927
Flash, COC, °C (°F)	D-92	-	-	223 (433)
Pour Point, °C (°F)	D-97	-	-18 (0)	-21 (-6)
Aniline Point, (°C) / °F	D-611	-	-	(80) 176
ASTM Color	D-1500	-	D 8.0	L 5.5
Sulfur, Mass %	D-4294	-	-	0.865
Refractive Index @ 20°C	D-1747	-	-	1.526
Volatility, %	EPA 24	-	-	0.8

The information on this Product Data Sheet is believed to be accurate and is typical of current production. Specifications are subject to change without notice.

Health And Safety Information See separate Safety Data Sheets available on request.

Cross™ is a trademark of Cross Oil Refining & Marketing, Inc., All other marks are property of their respective owners.

Cross Oil Refining & Marketing, Inc.

Smackover, AR 71762 | USA | Phone 800 864-6275 | www.crossoil.com

Product Data Sheet Revision 01/2002